

SJ DIT-6







CONNECTION WITH HEXAGONAL THREAD

Threaded Connection, Hexagonal Design

Model: DIT-6

Product Description

- Detachable design for easy cleaning and maintenance
- Often used in cement plants and the petrochemical equipment industry



Prodict Specification

Process connection

1/4、3/8"、1/2"、3/4"、1" PT, G, NPT, M

Instrument connection

1/4", 3/8", 1/2" PT, G, NPT, M

Scale ranges

0 ... 10 bar to 0 ... 250 bar, or all other equivalent pressure ranges

Material

Body: 316L SS

Diaphragm: 316L SS

Medium temperature


0°C ... 80°C (standard) , 81°C ... 200°C, 201°C ... 400°C

Others

Welded with instrument



Dimensions



Dimensions (mm)						
1	2	3				
<i>φ</i> 50	1/4"	13				
	3/8"	15				
	1/2"	20				
	3/4"	20				
	1"	23				

Assembling Drawing



X Ordering information

Model / Process connection / Connection location of pressure gauge / Nominal size / Scale range / Options

For any changes to the specifications of this catalogue, the latest version shall prevail.

SIN JIA ENTERPRISE COMPANY LIMITED

TEL:+886-2-2550-4512 FAX:+886-2-2550-4510 info@sinjiagauge.com www.sj-gauge.com

No.3, Ln. 71, Chifeng St., Datong Dist., Taipei City 103, Taiwan







MEXICO BRANCH OFFICE

Roberto Diaz No. 401 Ciudad Industrial Aguascalientes, Ags. México 20290

(449) 171 3420 www.4ManPro.com/SPA/



USA BRANCH OFFICE Pennzoil Place 700 Milam Suite 1300 Houston, Tx, USA 77002

+1 (832) 871 5022 www.4ManPro.com/ENG/

Aemonto For Manufacturing Processes

For any changes to the specifications of this catalogue, the latest version shall prevail. Copyright © 12/2019 by SIN JIA ENTERPRISE COMPANY LIMITED. All rights reserved.

