

SJ DIT-W







CONNECTION
WITH
WELDED THREAD

Threaded Connection, Welded Type

Model: DIT-W

Product Description

- Fully welded design, without additional sealing
- For hot, hazardous or toxic media
- Mostly used in oil, gas and petrochemical industries



Left: 48 mm Bottom: 90 mm

Right: 70 mm

Product Specification

Diameter

48 mm, 70 mm, 82 mm, 90 mm

Process connection

Male, female, union nut and loose threaded 1/4", 3/8", 1/2", 3/4", 1"

PT, G, NPT, M

Instrument connection

1/4", 3/8", 1/2" PT, G, NPT, M

Scale ranges

48 mm

Pressure gauge:

0 ... 4 bar to 0 ... 40 bar

Transmitter:

0 ... 4 bar to 0 ... 40 bar

70 mm

Pressure gauge:

0 ... 2.5 bar to 0 ... 60 bar

Transmitter:

0 ... 0.01 bar to -1 ... 60 bar

82 mm

Pressure gauge:

-1 ... 0 bar to -1 ... 40 bar

90 mm

Pressure gauge:

-1 ... 0 bar to -1 ... 60 bar

Transmitter:

0 ... 0.01 bar to -1 ... 60 bar

or all other equivalent vacuum or

combined pressure and vacuum

ranges



Product Specification

Material


Body: 304 SS, 316 SS, 316L SS, Dual Phase Steel, Hastelloy C276, Tantalum, Monel 400, Titanium, Nickel 200 Diaphragm: 316L SS, Hastelloy C276, Tantalum, Monel 400, Titanium, Nickel 200

Medium temperature


0°C ... 80°C (standard) , 81°C ... 200°C, 201°C ... 400°C


Others

Welded with instrument, flush port




Dimensions (mm)					
1)	2	3	(4)		
<i>φ</i> 48	1/2" NPT	68	22		







Dimensions (mm)						
1	2	3	4	(5)	6	Ø
arphi 70 $arphi$ 90	1/4"	63	22	15	50	22
	3/8"	65	22	15	50	22
	1/2"	68	22	15	50	30
	3/4"	70	27	20	55	32
	1"	71	35	21	56	38




Dimensions (mm)						
1	2	3	4	(5)		
	1/4"	64	29	22		
arphi 70 $arphi$ 90	3/8"	66	31	22		
	1/2"	69	34	30		
	3/4"	71	36	32		
	1"	74	39	38		







Dimensions (mm)						
1	2	3	4	(5)	6	7
arphi 70 $arphi$ 90	1/4"	88	22	15	75	22
	3/8"	90	22	15	75	22
	1/2"	93	22	15	75	30
	3/4"	95	27	20	80	32
	1"	96	35	21	81	38




Dimensions (mm)						
1	2	3	4	(5)		
	1/4"	89	29	22		
φ 70 φ 90	3/8"	91	31	22		
	1/2"	94	34	30		
	3/4"	96	36	32		
	1"	99	39	38		






Dimensions (mm)						
1	2	3	4	(5)	6	7
arphi 70 $arphi$ 90	1/4"	78	22	15	65	22
	3/8"	80	22	15	65	22
	1/2"	83	22	15	65	30
	3/4"	85	27	20	70	32
	1"	86	35	21	71	38



Dimensions (mm)						
1	2	3	4	(5)		
	1/4"	79	29	22		
φ 70 φ 90	3/8"	81	31	22		
	1/2"	84	34	30		
	3/4"	86	36	32		
	1"	89	39	38		



Dimensions (mm)					
1 2 3 4 5					
<i>φ</i> 82	19.5	80	22.7	24	

X Ordering information

Model / Diameter / Process connection / Material / Connection location of pressure gauge / Nominal size / Scale range / Options

For any changes to the specifications of this catalogue, the latest version shall prevail.

SIN JIA ENTERPRISE COMPANY LIMITED

TEL:+886-2-2550-4512 FAX:+886-2-2550-4510 info@sinjiagauge.com www.sj-gauge.com

No.3, Ln. 71, Chifeng St., Datong Dist., Taipei City 103, Taiwan







MEXICO BRANCH OFFICE

Roberto Diaz No. 401 Ciudad Industrial Aguascalientes, Ags. México 20290

4ManPro@4ManPro.com (449) 171 3420 www.4ManPro.com/SPA/



USA BRANCH OFFICE Pennzoil Place 700 Milam

Pennzoil Place 700 Milam Suite 1300 Houston, Tx, USA 77002

4ManPro-USA@4ManPro.com +1 (832) 871 5022 www.4ManPro.com/ENG/

Aemente For Manufacturing Proceedes

For any changes to the specifications of this catalogue , the latest version shall prevail. Copyright © 12/2019 by SIN JIA ENTERPRISE COMPANY LIMITED. All rights reserved.

