



SJ MSSMP858- TSDS

**TRANSMISOR
DE PRESIÓN
HIGIÉNICO**



Product introduction

Description



Standard



High-temperature

Hygienic pressure transmitter

Hygienic pressure transmitter, designed for food and pharmaceutical industry, is suitable for CIP/SIP cleaning and sterilization. Smart compact design, the welded process diaphragm medium parts is made of high quality stainless steel 316L, roughness $\leq 0.4\mu\text{m}$, filling fluid with hygiene standard in line with FDA certification, variety of international standard process connections are available.

Main parameters

Pressure types	Gauge pressure
Measuring range	10kPa-3MPa, please refer to the ordering information chapter
Output signal	4-20mA, 4-20mA+HART, 0.5-4.5VDC, Modbus-RTU/RS485, customer
Reference accuracy	$\pm 0.2\%$ URL, $\pm 0.5\%$ URL, customer

Measuring medium

Viscous, paste-like, adhesive, crystallising, particulates containing and contaminated media

Field of application

Pressure, level

Approvals





Technical specifications

Measuring range and limit

Nominal value	Smallest calibratable span	Lower range limit (LRL)	Upper range limit (URL)	Over pressure limit
40kPa	10kPa	-40kPa	40kPa	1MPa
250kPa	40kPa	-100kPa	250kPa	4MPa
1MPa	250kPa	-100kPa	1MPa	6MPa
3MPa	1MPa	-100kPa	3MPa	15MPa

The unit of the measuring range above can be converted into kg/cm², MPa and kPa. Provide other measuring range according to requirements. Adjust requirements: lower range value (LRV) and upper range value (URV) can be adjusted within the scope of the upper and lower range limit, minimum measuring range $\leq |URV - LRV| \leq$ maximum measuring range.

*Limit value of overpressure: depends on the pressure value of the parts with lowest pressure capacity

Standard specifications and reference conditions

Test standard: GB/T28474 / IEC60770; Zero based-calibration span, Linear output, Silicone oil filling, 316L stainless steel isolation diaphragm.

Performance specifications

The overall performance including but not limited to 【reference accuracy】, 【environment temperature effects】 and other comprehensive error

Typical accuracy: $\pm 0.2\text{URL}$

Stability: $\pm 0.2\%$ URL/ year

Reference accuracy

Including linearity, hysteresis and repeatability.
calibration temperature: $20^{\circ}\text{C} \pm 5^{\circ}\text{C}$

Linear output accuracy	Typical value	$\pm 0.2\%\text{URL}$	Nominal value: 40kPa, 250kPa 1MPa, 3MPa
	Max value/ voltage output	$\pm 0.5\%\text{URL}$	

Ambient temperature effects(Typical)

Within the range - 20-80°C total impact	$\pm 0.2\%\text{URL}/10\text{k}$
---	----------------------------------

Power supply effects

Zero and span change should not be more than $\pm 0.005\%$ URL/V when power supply changes in 10.5/16.5-55VDC

Loading effects

Zero and span change should not be more than $\pm 0.05\%$ URL/k Ω

Vibration effects

Vibration resistance	According to IEC60068-2-6 , 10g RMS (25-2000HZ)
Impact resistance	According to IEC60068-2-27 , 500g/1ms

Output signal

Signal	Type	Output
4-20mA	Linearity	Two wire
4-20mA+HART	Linearity	Two wire
0.5-4.5VDC	Linearity	Three wire
Modbus-RTU/RS485	Linearity	Four wire

Insulation resistance

$\geq 20\text{M}\Omega@, 100\text{VDC}$



Technical specifications

Damping time

Total damping time constant: equal to the sum of damping time of amplifier and sensor capsule
Damping time of amplifier : 0-100S adjustable
Diaphragm capsule (isolation diaphragm and silicon oil filling) damping time: $\leq 0.2S$
Startup after power off : $\leq 3S$ (with HART communication: $\leq 0.2S$)
Normal services after data recovery: $\leq 4S$ (with HART communication: $\leq 31S$)

Environment condition

Items	Operational condition
Media temperature	-40-85°C
Storage temperature	-40-100°C
isolated filling fluid temperature	Sanitary fluid filling : -10-125°C; with heat exchange connector: -10-250°C* Silicon oil filling: -40-120°C, with heat exchange connector: -40-300°C*
Working humidity	0-95%RH
Protection class	IP67
Dangerous condition	ExialICT4(GYB16.1965X)**
*Using heat exchange connector may lead to zero offset and temperature drift. The degree depends on mounting position and filling fluid	
**Please contact the engineer for further information	

Technical Specifications

Signal output	4-20mA	4-20mA+HART*	0.5-4.5VDC	0.5-4.5VDC(ratiometric output)	RS485
Power supply voltage	10-30VDC	10.5/16.5-55VDC	6-15VDC	5VDC	5VDC/9-30VDC
Electric current	$\leq 20.8mA$		$\leq 3.5mA$		$\leq 7mA$
Load resistance(Ω)	$< (U-10)/0.0208$	$< (U-10.5)/0.0208^{**}$	$\geq 5k$, recommend 100k		/
Transmission distance	$< 1000m$		$< 5m$		$< 1200m$
Power consumption	$\leq 500mW(20.8mA \text{ output}@24VDC)$		$\leq 42mW(0.5-4.5VDC \text{ output}, 12VDC)$		$\leq 168mW(RS485 \text{ output}@24VDC)$

*For this output type, the load resistance value in communication is 250 Ω

**The load resistance value 0-2119 Ω is in nominal working condition, 250-600 Ω is HART communication

EMC environment(not RS485 signal output)

NO.	Test items	Basic standards	Test conditions	Performance level
1	Radiated interference	GB/T 9254/CISPR22	30MHz-1000MHz	OK
2	Conducted interference (DC power port)	GB/T 9254/CISPR22	0.15MHz-30MHz	OK
3	Electrostatic discharge immunity test (ESD)	GB/T 17626.2/IEC61000-4-2	4kV(Contact), 8kV(Air)	B(Note2)
4	Immunity to radio frequency EM-fields	GB/T 17626.3/IEC61000-4-3	10V/m(80MHz-1GHz)	A(Note1)
5	Power frequency magnetic field Immunity test	GB/T 17626.8/IEC61000-4-8	30A/m	A(Note1)
6	Electrical fast transient / Burst Immunity test	GB/T 17626.4/IEC61000-4-4	2kV(5/50ns, 100kHz)	B(Note2)
7	Surge immunity requirements	GB/T 17626.5/IEC61000-4-5	1kV(Line to line) 2kV(Line to ground) (1.2us/50us)	B(Note2)
8	Immunity to conducted disturbances induced by radio frequency fields	GB/T 17626.6/IEC61000-4-6	3V(150kHz-80MHz)	A(Note1)

(Note 1) Performance level A: The performance within the limits of normal technical specifications.

(Note 2) Performance level B: Temporary reduction or loss of functionality or performance, it can restore itself. The actual operating conditions, storage and data will not be changed.

For any changes to the specifications of this catalogue, the latest version shall prevail.



Product selection instruction

Sensor select instruction

Code	Nominal value	Description
L403G	40kPa	Range 0kPa-35kPa, smallest calibratable span 10kPa
L254G	250kPa	Range 0kPa-200kPa, smallest calibratable span 25kPa
L105G	1MPa	Range 0kPa-1MPa, smallest calibratable span 100kPa
L305G	3MPa	Range 0kPa-3.5MPa, smallest calibratable span 300kPa
Adjust requirements: lower range value (LRV) and upper range value (URV) can be adjusted within the scope of the upper and lower range limit, minimum measuring range≤ URV - LRV ≤maximum measuring range		

Code	Position	Instruction
F	Sensor seal	Stainless steel welding seal

Electrical connection


Code	Description
D1	DIN43650 connector, IP65

DIN43650(D1)



Electrical connection

DIN43650(D 1)



Label	Two wires	Three wires	Four wires	Modbus-RTU/RS485
1	Power+	Power+	Power+	Power+
2	Power+	Power-	Power-	Power-
3	Key-z	Signal+	Signal+	A+
			Signal-	B-


Note: Key-z is modified zero pressure

Product selection instruction

Transmission module

Code	Description
F	4-20mA two wire, power supply: 10-30VDC
H	4-20mA+HART two wire, power supply: 16.5-55VDC
R	Modbus-RTU/RS485 5V/9-30VDC
5	0.5-4.5VDC three wire, power supply: 6-15VDC
6	0.5-4.5VDC three wire, proportional output power supply: 5VDC
A	4-20mA two wire, intrinsic safety, power supply: 10-30VDC

Cooling element connector (HT)




Process connection select instruction


Code	Items	Description
4	Process connector material	Stainless steel, SUS304
6		Stainless steel, SUS316
NT	Connection type	Standard connection, medium temperature: -25-85°C
HT		Cooling element connector, medium temperature: -40-150°C
F	Isolation fluid filling	Sanitary fluid filling, Neobee M-20
S		Silicon oil filling
S	Isolation diaphragm material	SUS316L
H		Hastelloy C
K01	Process connection specifications	Tri-Clamp 1-1/2"
K02		Tri-Clamp 2"
K03		DIN32676 DN32
K04		DIN32676 DN40
K05		DIN32676 DN50
K06		ISO2852 DN38
K07		ISO2852 DN40
K08		ISO2852 DN51
K09		DIN11851 DN25
K10		DIN11851 DN40
K11		DIN11851 DN50
K12		SMS DN1-1/2"
K13		SMS DN2"
K14		IDF DN1-1/2"
K15		IDF DN2"
K18		DRD
K20		Plug in tube flush sanitary clamp

Product drawing and dimension

Standard drawing and dimension with
DIN43650 (D1) (unit:mm)




High-temperature drawing and dimension with
DIN43650 (D1) (unit:mm)




Product drawing and dimension


Process connection (K01-K08)(unit: mm)




Process connection (K09-K11)(unit: mm)



Process connection (K12-K13)(unit: mm)




Process connection (K14-K15)(unit: mm)






Product drawing and dimension

Process connection (K18) (unit: mm)



Process connection (K20) (unit: mm)




For any changes to the specifications of this catalogue, the latest version shall prevail.




Product drawing and dimension


Tri-Clamp (G1-G2) (unit: mm)



Seal ring (M1-M2) (unit: mm)



Welding adaptor(Z1-Z1)(unit:mm)





Ordering information chapter

Item	Parameters	Code	Instruction	(*) Fast delivery available
	Model	MSSMP858-TSD	Monosilicon gauge pressure transmitter	
Sensor	Separator	-	Detailed specifications as following	
	Pressure range code	S403G	Nominal value(URL): 40kPa	
		S254G	Nominal value(URL): 250kPa	
		S105G	Nominal value(URL): 1MPa	*
		S305G	Nominal value(URL): 3MPa	
	Sensor seal	F	Stainless steel welding seal	
Electrical connection	Separator	-	Detailed specifications as following	
	Electrical connection	D1	DIN43650 connector, IP65	*
	Cable entry protector	R0	None	
Output	Separator	-	Detailed specifications as following	
	Output signal	F	4-20mA two wire, power supply: 10-30VDC	*
		H	4-20mA+HART two wire, power supply: 16.5-55VDC	*
		R	Modbus-RTU/RS485 5V/9-30VDC	
		5	0.5-4.5VDC three wire, power supply: 6-15VDC	
		6	0.5-4.5VDC three wire, ratiometric output, power supply: 5VDC	
		A	4-20mA two wire, intrinsic safety, power supply: 10-30VDC	
Body tube	Separator	-	Detailed specifications as following	
	Tube	53	Stainless steel tube length: 53mm (HART, Modbus-TRU/RS485 is not available)	*
		65	Stainless steel tube length: 65mm (HART, Modbus-TRU/RS485 is not available)	*
		85	Stainless steel tube length: 85mm (with HART、 Modbus- TRU/RS485)	
Process connection	Separator	-	Detailed specifications as following	
	Process connector material	4	Stainless steel, SUS304	*
		6	Stainless steel, SUS316	
	Connection type	NT	Standard connection, medium temperature: -25-85℃	
		HT	Cooling element connector, medium temperature: -40-150℃	*
	Isolation fluid filling	F	Sanitary fluid filling, Neobee M-20	*
		S	Silicon oil filling, process temperature: -45-205℃	*



Ordering information chapter

	Isolation diaphragm material	S	SUS316L	
		H	Hastelloy C	
	Process connection specifications	K01	Tri-Clamp 1-1/2", max measuring range 2MPa	*
		K02	Tri-Clamp 2", max measuring range 2MPa	*
		K03	DIN32676 DN32, max measuring range 1.6MPa	
		K04	DIN32676 DN40, max measuring range 1.6MPa	
		K05	DIN32676 DN50, max measuring range 1.6MPa	
		K06	ISO2852 DN38, max measuring range 4MPa	
		K07	ISO2852 DN40, max measuring range 4MPa	
		K08	ISO2852 DN51, max measuring range 2.5MPa	
		K09	DIN11851 DN25, max measuring range 2.5MPa	
		K10	DIN11851 DN40, max measuring range 2.5MPa	
		K11	DIN11851 DN50, max measuring range 2.5MPa	
		K12	SMS DN1-1/2", max measuring range 2.5MPa	
		K13	SMS DN2", max measuring range 2.5MPa	
		K14	IDF DN1-1/2", max measuring range 2MPa	
		K15	IDF DN2", max measuring range 2MPa	
		K18	DRD, max measuring range 2.5MPa	
		K20	Plug in tube flush sanitary clamp, max measuring range 2MPa	
Additional options	Separator	-	Detailed specifications as following	
	Process connection accessory	/G1	1.5" Tri-clamp	*
		/G2	2" Tri-clamp	*
		/M1	1.5" sealing gasket, material: silicon rubber, process temperature range: -60-200°C	*
		/M2	2" sealing gasket, material: silicon rubber, process temperature range: -60-200°C	*
		/Z1	Welding adaptor, Tri-Clamp1-1/2"	
		/Z2	Welding adaptor, Tri-Clamp2"	*
	Calibration report	/Q1	Calibration report provided by our company	*
	Approvals (multiple)	/I1	Intrinsic safety certificate, ExiaIICT4, NEPSI	*
		/F3	CE certificate	
	Wetted parts treatment	/G1	Ungrease treatment	
		/G2	Electropolishing treatment	



Approvals

Factory certificate

Certification organization	Intertek
Quality management system	ISO9001-2015
Scope of certification	Design and production of pressure transmitter
Registration number	110804039

CE

Certificate organization	ISET
License scope	MSSMP858 series pressure transmitter
Mark	CE
EMC instruction	2014/30/EU
Standard	EN61326-1: 2013
Registered number	IT051353LG161207

Intrinsic safety certificate

Certification organization name	NEPSI
Licenses range	MSSMP858 series pressure transmitter
Explosion-proof mark	ExiaIICT4
Ambient temperature	-40-+60°C
Medium maximum temperature	+120°C
Registration number	GYB16.1965X
Intrinsically safe parameter description	Maximum input voltage:28VDC
	Maximum input current:100mA
	Maximum input power:0.7w
	Maximum internal equivalent parametersCi(nF):0
	Maximum internal equivalent parametersLi(mH):0



SIN JIA ENTERPRISE COMPANY LIMITED

TEL:+886-2-2550-4512

FAX:+886-2-2550-4510

info@sinjiagauge.com

www.sj-gauge.com

No.3, Ln. 71, Chifeng St., Datong Dist., Taipei City 103, Taiwan

For any changes to the specifications of this catalogue,the latest version shall prevail.

4ManPro

*Elements For
Manufacturing Processes*



MEXICO BRANCH OFFICE

Roberto Diaz No. 401
Ciudad Industrial
Aguascalientes, Ags.
México
20290

4ManPro@4ManPro.com
(449) 171 3420
www.4ManPro.com/SPA/



USA BRANCH OFFICE

Pennzoil Place
700 Milam
Suite 1300
Houston, Tx, USA
77002

4ManPro-USA@4ManPro.com
+1 (832) 871 5022
www.4ManPro.com/ENG/

*Elements For
Manufacturing Processes*

For any changes to the specifications of this catalogue , the latest version shall prevail.

Copyright © 12/2019 by SIN JIA ENTERPRISE COMPANY LIMITED. All rights reserved.

